

26. THE CONTRACTOR SHALL COORDINATE WITH NV ENERGY IN PROVIDING SERVICE FOR THE SIGNAL WITHIN NV ENERGY STANDARDS.
27. POWER PANEL SURGE PROTECTION SHALL BE PROVIDED AND APPROVED THROUGH THE SUBMITTAL PROCESS TO THE PUBLIC WORKS TRAFFIC ENGINEERING DIVISION.
28. EXISTING VEHICLE DETECTOR LOOPS DAMAGED BY THE CONTRACTOR SHALL BE REPLACED AND MADE FULLY FUNCTIONAL WITHIN TWO WORKING DAYS. IF NOT MADE FUNCTIONAL WITHIN THE TWO DAYS FOLLOWING DAMAGE, THE CITY MAY PERFORM THE REPAIR AND BACK-CHARGE THE CONTRACTOR AT THE EXPENSE OF \$1000 PER LOOP. SPlicing WILL NOT BE CONSIDERED AS AN ADEQUATE REPAIR.
29. THE CONTRACTOR SHALL COORDINATE TRAFFIC SIGNAL INSTALLATIONS OR MODIFICATIONS WITH THE CITY OF SPARKS TRAFFIC ENGINEER AT (775) 353-7863.
30. NO SPLICES SHALL BE PERMITTED BETWEEN THE CONTROLLER CABINET AND THE TRAFFIC SIGNAL POLE. ALL CONNECTIONS SHALL BE MADE AT THE JUNCTION BOX, OR IN THE CASE OF LOOPS, AT THE LOOP STUB. ANY DEVIATION TO THIS REQUIREMENT SHALL BE APPROVED BY THE TRAFFIC ENGINEER PRIOR TO THE WORK.
31. VEHICLE DETECTOR LOOPS DAMAGED DURING CONSTRUCTION WHICH ARE PERMITTED BY THE TRAFFIC ENGINEER TO BE TEMPORARILY SPliced, MUST BE REPLACED PRIOR TO FINAL ACCEPTANCE.
32. IF ANY PAVEMENTS MARKINGS ARE TO BE RELOCATED, VEHICLE DETECTOR LOOPS SHALL BE RELOCATED ACCORDINGLY TO REMAIN CONSISTENT WITH CITY OF SPARKS STANDARD DETAIL NO. S-405A AND NO. S-405B.
33. AS A PART OF ANY STREET WIDENING PROJECT OR THE ADDITION OF ANY STREET TRAVEL LANES TO EXISTING LANES, SUCH AS TURN LANES, ACCELERATION OR DECELERATION LANES, ETC., THE CONTRACTOR MUST EXTEND ANY TRAFFIC CONTROL CONDUITS AND/OR WIRING AND REPLACE ALL AFFECTED VEHICLE LOOP DETECTOR WIRING (SPlicing SHALL NOT BE ALLOWED).
34. SIGNAL EQUIPMENT SHALL BE PROVIDED AND APPROVED THROUGH THE SUBMITTAL PROCESS TO THE PUBLIC WORKS TRAFFIC ENGINEERING DIVISION.
35. FOR POLE DETAILS NOT SHOWN, SEE POLE MANUFACTURER'S DETAILED DRAWINGS.
36. ALL SIGNAL POLES SHALL CONFORM TO NDOT TYPE 35 AND 35A SPECIFICATIONS, INCLUDING BOLT CIRCLE DIMENSIONS, ANCHOR BOLTS, AND FOOTING DIMENSIONS.
37. FINAL POLE APPROVAL AND SUBMITTALS TO BE APPROVED BY THE CITY OF SPARKS.
38. CLAM SHELL FOR TYPE 7D POLE TO BE USED ONLY WHEN POLE IS INCLUDED AS A SIGNAL POLE. DO NOT USE CLAM SHELL WHEN TYPE 7D POLE IS USED IN SERIES LIGHTING.
39. POLE MAY BE MANUFACTURED AS EITHER A DOUBLE OF SINGLE CANDYCANE CONFIGURATION.
40. VIDEO DETECTION MAY BE USED IF APPROVED BY THE CITY TRAFFIC ENGINEER.

STANDARD DETAILS FOR PUBLIC WORKS CONSTRUCTION

DRAWING No.



NOTES - TRAFFIC SIGNALS & POLES

S-407F

APPROVED BY: JE DATE: 1/2020